

## Linux-Ready Cortex-A5 Surge-Protected Industrial IoT Gateway

# Matrix-704



### Features

- ATTEL Cortex-A5 ATSAMA5D35 536MHz CPU
- Linux Kernel 4.19.x with File System
- Toolchain gcc 8.2.0 + glibc 2.28
- 512MB LPDDR2 SDRAM
- 16GB eMMC Flash
- 1 x Gigabit Ethernet and 1 x 10/100Mbps Ethernet
- 1 x Full Size miniPCIe Socket Inside, 1 x Micro-SIM Slot Inside
- 2 x Antenna Through SMA Connector Holes Reserved
- 1 x Micro-SD Card Inside for Data Backup
- 4 x RS-485 Serial ports with Surge Protection
- Optional RS-485 with Isolation and Surge Protection

### ■ H/W Specifications

#### CPU / Memory

- CPU: ATTEL ATSAMA5D35 536MHz w/MMU
- SDRAM: 512MB, LPDDR2
- Flash: 16GB, eMMC

#### Network Interface

- Type: 1 x Gigabit and 1 x 10/100Mbps Ethernet
- Protection: 1.5KV magnetic isolation
- Connector Type: RJ45

#### USB 2.0 Host Interface

- Host Ports: 1
- Supports 480Mbps hi-speed mode

#### Console / Debug Ports

- Support microUSB console port
- Serial console port (inside the box)

#### TTY (Serial) Ports

- 4 x Surge-protected RS-485 (No isolation)
- Optional: 4 x Isolated / Surge-protected RS-485 (2500Vrms isolation)
- Direction Control: Auto, by hardware
- Connector: Terminal block

#### TTY (Serial) Port Parameters

- Baud Rate: Up to 921.6Kbps
- Parity: None, Even, Odd, Mark, Space
- Data Bits: 5, 6, 7, 8
- Stop Bits: 1, 1.5, 2
- Flow Control: RTS / CTS, XON / XOFF, None

#### SD Slot

- 1 x microSD socket, support up to 128G storage capacity
- SD 2.0 compliant, supports SDHC

#### Expansion

- 1 x miniPCIe Full-size socket
- 1 x micro-SIM card socket
- 2 x SMA type Antenna holes reserved

#### Power Requirement

- Input Voltage: +9V~+48VDC (terminal block)
- DC+12VDC (DC Jack)

#### General

- Real-time clock(RTC): Yes
- Watchdog: Yes
- Dimensions (W x H x D): 140 x 119.5 x 35.2mm (5.5 x 4.7 x 1.38in)
- Operating Temperature: 0~70°C (32~158°F)
- Regulation: CE Class A, FCC Class A

### ■ S/W Specifications

#### Operation System

- Linux kernel 4.19.x
- Support bootup from eMMC or SD card
- Boot Loader : BareBox
- File System : ETX4

#### Software Development

- Toolchain: gcc 8.2.0 + glibc 2.28
- Supports in-place C/C++ code compilation

#### Package Management

- Package repository: Artila self-maintained repository
- Command: Using standard apt-get command

#### Popular Packages

- Web server: Apache / Nginx / Lighttpd
- Database: MySQL / SQLite3 / PostgreSQL
- Script Language: PHP / Python / Perl / NodeJS
- Text editor: vim / nano / sed
- Administration: Webmin

### ■ Ordering Information

#### Matrix-704

- Linux-ready Cortex-A5 536MHz Surge-protected Industrial IoT Gateway with 512MB SDRAM, 16GB eMMC Flash with 4 x Surge-protected RS-485 serial ports

#### CB-PHDF9-050 (91-PHDF9-050)

- Console Cable (Wafer Box to DB9 Female, 50cm)

#### DK-35A (36-DK35A-000)

- DIN RAIL Mounting Kit

#### PWR-12V-1A

- 100~240VAC to 12VDC 1A Power Adapter

### ■ Mounting

